Daniel W. Kuderna
CECOM Intelligence & Information Warfare Directorate
daniel.kuderna@mail1.monmouth.army.mil
732-427-5719

Tactical UAV SAR/MTI Radar

Ku Band
65 lbs.
530 W



TUAVR CONOPS

Reconnaissance, Surveillance, Targeting & BDA



Multi-Mode Tactical UAV MTI





- Range to 15 km
- Prob of Detection 75%
- False Alarm Rate £ 2/min
- TLE 100m at 11 km
- Coverage 1200km²/hr

SAR Strip Map Mode 2



- Swath Width - 400 to 1200M
- Variable Resolution - 0.3 - 1.0 meter
- 3 Ft Res Search, Image Target at 1 Ft
- CEP - 23 to 28M
- Range to 12 km
- Map Way Point to Way Point

SAR Strip Map Mode 1



- Swath Width - 400 to 1200M
- Variable Resolution - 0.3 - 1.0 meter
- 3 Ft Res Search, Image Target at 1 Ft
- CEP - 23 to 28M
- Range to 12 km
- Fixed Depression

Spot-Light Mode



- **Multiple Images at Multiple Angles**
- **Spot Size**
  - **400x400m(1 Ft Res)**
  - **1200x1200m (3Ft Res)**
- **CEP - 23 to 28M**
- **Range - to 12km**

Versatile Organic RSTA Capability for FCS Commander

SAR 1.0m Resolution Imagery



SAR 0.3m Resolution Imagery

SAR Overcomes Environmental Conditions

EO



Clear Sky, Daylight

IR



Clear Sky, Day or Night, Below Clouds

SAR



Clear /Adverse Conditions Day or Night, Through Clouds

Conclusions

- Active Sensors provide Continuous ISR in Adverse Atmospheric Conditions
- Extends Engagement Horizon beyond Enemy's Range
- Provides Real-time ISR&T Directly to Field Commanders
- Multi-Mode Sensors Reduce Force Structure and Logistics Trail
- Permits Continuous BDA Throughout an Engagement